



Silk Series Home Wallbox

The Silk Series Home Wallbox is a stylish and user-friendly charging solution with a SAE 1772 (Type 1) connector and smart app integration for easy installation and use. UL-certified, dustproof, and waterproof, ensures the top priority of EV charging safety. In addition, Silk Series wins Red Dot Award for its distinctive design, it also offers intelligent load management and seamless PV integration for optimized energy usage.

US Standard



10kW



Pearl White



Starry Black



12kW



Space Gray

Flexible Options

- Wall-mount / pole-mount
- Hardwired / NEMA plug
- 4 enclosure colors
- Multiple charging modes

Environmental Friendly

- Certified by Energy Star
- Eco-friendly enclosure materials

High Reliability

- Anti-welding protection
- NEMA 4 dustproof and waterproof design
- CCID 20 leakage current protection
- UL listed and CSA certified

Smart Operation

- Multi communications (Wi-Fi / Bluetooth / Ethernet)
- Scheduled charging



10kW Plug&Play





Silk Series Home Wallbox

Datasheet	Model	AC010K-AU-35	AC012K-HU-35
Electrical Specification	Power Supply	L1+L2+G	
	Rated Voltage	240V AC	
	Max Current	40A	50A
	Frequency	60Hz	
	Max Power	10kW	12kW
Basic Attributes	Wiring Type	NEMA 14-50P	Hardwired
	Charge Connector	SAE 1772 (Type 1)	
	Cable Length	7m (23 feet) / 7.5m (25 feet)	
	Enclosure	PC943	
	Color	White Front Cover: PANTONE RAL 9003 Back Cover: PANTONE White C Black (PANTONE Black C)	Space Gray Front Cover: PANTONE 10452 C Back Cover: PANTONE Coolgray 9C
Interactive Interface	Installation	Wall-mount / Pole-mount (Optional)	
	LED Indicator	Green / Yellow / Red	
	RFID Reader	MIFARE ISO/IEC 14443A	
Communication	Start Mode	Plug & Charge / RFID Card / App	
	Wi-Fi & Bluetooth & Ethernet	Standard	
	OCPP	OCPP 1.6 Json	
Safety	Leakage Current Protection	CCID 20	
	Enclosure Rating	NEMA 4	
	Impact Protection	IK08	
	Electrical Protection	Overcurrent protection, Residual current protection Surge protection, Over / Under voltage protection, Over temperature protection	
	Certification	UL / FCC / Energy Star	CSA / FCC / Energy Star
	Certification Standard	UL2594 UL2231-1 UL2231-2 FCC Part 15B	
	Warranty	2 Years	
Working Environment	Operation Temperature	-30°C ~+50°C (-22 °F -122 °F)	
	Work Humidity	5%-95%	
	Work Altitude	≤2000m	
Package	Product Dimension	344 x 192 x 101mm (H x W x D)	
	Net Weight	6 kg	6 kg
	Gross Weight	8 kg	7 kg
	External Package	Carton	

